ARM STITCH

FIBC/BIG BAG SEWING MACHINE



AS - 603 DR

TECHNICAL DETAIL:

SINGLE NEEDLE, PLAIN FEED, DOUBLE THREAD, DOUBLE LOCKED CHAIN STITCH SEWING MACHINE.



AS-603 DR

APPLICATION:

For Seaming & Hemming Of Light to Heavy Weight Fabrics Such As PP/HDPE Woven Cloth. For Sews Over the Belt on the CONTAINER BAGS. For Top Sewing on the Container Bags (Filler Cord From Top & Below Can Be Stitched For Sealing Needle Punctures).

AS - 603 UDR-N

TECHNICAL DETAIL:

SINGLE NEEDLE, PLAIN FEED, DOUBLE THREAD, HEAVY DUTY CHAIN STITCH SEWING MACHINE WITH SYNCHRONIZED UPPERFEED, ALTERNATING UPPER FEED DOG AND PRESSURE FOOT.



For Even Matched Side Seams On Heavy Weigh Fabrics. Applicable For All Seams on Container Bags. Side Seams, Inserting Top Cover, Attaching Filling & Discharging Tubes With Filler Cord From The Top & From Below For Sealing Needle Punctures.





AS-603 UDR-N

TECHNICAL PARAMETERS:

MODEL	MAX. SPEED (R.P.M.) APPROX.	WORKING SPEED (R.P.M.) APPROX.	STITCH RANGE (100 MM)	SEWING CAPACITY (MM)	NEEDLE SIZE	NO. OF NEEDLES	NO. OF THREAD	STITCHING THREAD TYPE	LUBRI -CATION	MOTOR
AS 603 DR	2000	1800 depends on Sewing Material	7 - 13 * Adjus -table	Up to 12 mm	DR x 2 #28 (Organ)	One	Two	Jute, PP Multi Filament, Fabricated Yarn	Semi Auto -matic	1 H.P., 1 or 3 phase 1425-2850 RPM
AS 603 UDR-N	1800	1600 depends on Sewing Material	6 - 13 * Adjus -table	Up to 15 mm	UY9848GS 29/120 (Schmetz)	One	Two	Multi Filament, Fabricated Yarn	Semi Auto -matic	1 H.P., 1 or 3 phase 1425-2850 RPM

Mfg. By



Plot No. 1106/1107, Phase III, D-Road, G.I.D.C., Vatwa, Ahmedabad - 382 445. GUJARAT-INDIA

Phone: +91-79-2583 4255, 2583 0432 Fax: +91-79-2583 2255

E-mail: daspanchal@armstitch.com • pritesh@armstitch.com • pratik@armstitch.com Website: www.armstitch.com